

DUCHESNE COUNTY MONUMENT SURVEY RECORD

T2S R3W

SEC 22	SEC 23
SEC 27	SEC 26

U.S.B.&M.

J-17

	22		

NO SCALE

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
LOCATED AT LAT: 40°18'23.57718"N & LONG:
110°13'58.14329"W USING THE UTAH STATE G.P.S.
VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND ORIGINAL MARKED STONE AND REBAR WITH ALUMINUM CAP
IN MOUND OF STONES AT SECTION CORNER



DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE
THE ORIGINAL LOCATION OF THE CORNER

REFERENCED AS SHOWN

STATE PLANE COORDINATE DATA
(U.S. SURVEY FEET)
NAD 83 UTAH CENTRAL ZONE
N: 7275896.85
E: 2003122.29

LATITUDE: 40°17'13.12338" N

LONGITUDE: 110°11'59.24196" W

PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300020S0030W0_500300

CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 8 FEB '16

Jerry D. Allred, Professional Land Surveyor
Certificate No. 148951
Duchesne County Surveyor

